



A HEAVY-DUTY
WET/DRY CONVERTIBLE
DRILL YOU CAN TRUST
ON THE JOB SITE

TECHNICAL SPECS

Power Input	110V-120V, 1700W (15A)
Voltage	110V-120V, 50Hz/60Hz
No Load min-1	930 / 1520 / 4270
Hand-held Capacity	3" (80mm)
Rig-Mounted Capacity	6" (152mm)
Spindle Thread External	1.25" UNC
Spindle Thread Internal	.5" BSP
Neck Diameter	2.25" (60 mm)
Length	17" (437mm)
Width	4.5" (115mm)
Height	11.5" (289mm)
Weight	14lbs (6.4kg)

FEATURES

- Wet and dry drilling capability
- Magnesium alloy construction for minimal weight and maximum strength
- Improved cooling and increased durability
- Soft start electric motor
- Current and thermal overload protection
- Load warning system and indicator light
- Protection Class I with PRCD
- 3 speed oil bath gearbox
- Mechanical clutch
- Integrated water feed system
- Can be mounted to a rig for larger drilling jobs
- Two-in-one spindle for both 1.25" UNC and .5"BSP
- Built-in anti-seize ring
- Anti-vibration side handle reduces operator stress
- Included wrench
- 5/8"-11 bit adapter
- Tool case
- Water feed
- Vacuum port



DMC6D



HCD2200



CDM4094



CDM4096