

# 12ES & 12DC

## SHOTBLASTER & DUST COLLECTOR



SPE 12ES  
SHOT BLASTER



SPE 12DC  
DUST COLLECTOR

TECHNICAL SPECS	SPE 12ES	12DC	DESIGN FEATURES
Voltage	380-415V	230V / 460V	<ul style="list-style-type: none"> <li>· Blast unit constructed of manganese steel</li> <li>· Dust collector fitted with integral compressor and reverse air jet pulsation system to allow continuous working</li> <li>· Blasting width can be reduced for line removal and weld inspection</li> <li>· Self propelled variable speed drive allows complete operator control</li> <li>· Grill fitted into hopper assembly to keep foreign objects from entering the blastwheel and causing damage</li> <li>· Capable of using up to S550 abrasive</li> <li>· Fully machined blastwheel support bearing assembly (eliminates bearing problems, automatically self-aligns blastwheel components)</li> <li>· Blastwheel can be rotated in both directions (Optional extra)</li> <li>· Can be dismantled to pass through a 24" (600mm) access hole in storage tanks</li> </ul>
Phase	3-Phase		
Blast Motor Output	10hp (7.5kW)	-	
Cycles	60Hz		
Cleaning Width	12" (305mm)	-	
Length	46.5" (1180mm)	68." (1730mm)	
Width	19" (480mm)	31.5" (800mm)	
Height	47" (1200mm)	63" (1600mm)	
Weight	704lbs (320kg)	770lbs (350kg)	
CFMS	-	1020/1220 ft <sup>3</sup> /min	



SPE 9G



SPE 9ES



SPE 12ES



SPE 16ES



SPE 20ES



SPE 20ES  
ELECTRIC DRIVE